

**KUGLASTA SLAVINA KPC - ISO
PUN PROTOK, DN25-DN200**

	<p>DN25-DN50</p> <p>CE</p>
	<p>DN65-DN150</p> <p>CE</p>
	<p>DN200</p> <p>CE</p>



Radna temperatura: -10 °C/+100 °C**Materijali**

1	Kućište	Nodularni liv – EN-GJS-400-15 (GGG40)
2	Kugla	Mesing – CuZn40Pb2 (Ms 58)
3	Vreteno	Nerdjajući čelik – X20Cr13 (A420)
4	Zaptivač	PTFE
5	O-Ring	NBR
6	Ručka	Čelik (pocinkovano) – S235JR (RSt 37-2)

KPC DN ... PN16 DP NX PB - ISO**PN16**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak K x h	Težina (kg)
A954243	25	125	115	76	25	150	18	85	14	4	F03	11 x 13,5	3,30
A954244	32	130	140	92	31	235	18	100	18	4	F04	14 x 18	5,40
A954245	40	140	150	97	39	235	18	110	18	4	F05	14 x 18	6,70
A954246	50	150	165	105	49	271	20	125	18	4	F05	14 x 18	8,90
A954247	65	170	185	124	63	288	18	145	18	4	F07	17 x 23	14,70
A954248	80	180	200	133	76	288	20	160	18	8	F07	17 x 23	20,10
A954249	100	190	220	153	100	288	20	180	18	8	F07	17 x 23	26,00
A954250	125	200	250	183	125	541	22	210	18	8	F10	22 x 27	30,00
A954333	125	325*	250	183	125	541	22	210	18	8	F10	22 x 27	34,70
A954331	150	210	285	203	150	541	22	240	22	8	F10	22 x 27	38,00
A954334	150	350*	285	203	150	541	22	240	22	8	F10	22 x 27	45,30
A954332	200	400*	340	316	200	1000	24	295	22	12	F12	22 x 27	85,00

KPC DN ... PN40 DP NX PB - ISO**PN40**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak K x h	Težina (kg)
A954243	25	125	115	76	25	150	18	85	14	4	F03	11 x 13,5	3,50
A954244	32	130	140	92	31	235	18	100	18	4	F04	14 x 18	5,30
A954245	40	140	150	97	39	235	18	110	18	4	F05	14 x 18	6,60
A954246	50	150	165	105	49	271	20	125	18	4	F05	14 x 18	8,80

Radna temperatura: -10 °C/+150 °C**Materijali**

1	Kućište	Nodularni liv – EN-GJS-400-15 (GGG40)
2	Kugla	Mesing – CuZn40Pb2 (Ms 58)
3	Vreteno	Nerdjajući čelik – X20Cr13 (A420)
4	Zaptivač	PTFE
5	O-Ring	EPDM
6	Ručka	Čelik (pocinkovano) – S235JR (RSt 37-2)

KPC DN ... PN16 DP EX PB - ISO**PN16**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak K x h	Težina (kg)
A954253	25	125	115	76	25	150	18	85	14	4	F03	11 x 13,5	3,30
A954254	32	130	140	92	31	235	18	100	18	4	F04	14 x 18	5,40
A954255	40	140	150	97	39	235	18	110	18	4	F05	14 x 18	6,70
A954256	50	150	165	105	49	271	20	125	18	4	F05	14 x 18	8,90
A954257	65	170	185	124	63	288	18	145	18	4	F07	17 x 23	14,70
A954258	80	180	200	133	76	288	20	160	18	8	F07	17 x 23	20,10
A954259	100	190	220	153	100	288	20	180	18	8	F07	17 x 23	26,00
A954260	125	200	250	183	125	541	22	210	18	8	F10	22 x 27	30,00
A954343	125	325*	250	183	125	541	22	210	18	8	F10	22 x 27	34,70
A954341	150	210	285	203	150	541	22	240	22	8	F10	22 x 27	38,00
A954344	150	350*	285	203	150	541	22	240	22	8	F10	22 x 27	45,30
A952024	200	400*	340	316	200	1000	24	295	22	12	F12	22 x 27	85,00

KPC DN ... PN40 DP EX PB - ISO**PN40**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak K x h	Težina (kg)
A954253	25	125	115	76	25	150	18	85	14	4	F03	11 x 13,5	3,30
A954254	32	130	140	92	31	235	18	100	18	4	F04	14 x 18	5,40
A954255	40	140	150	97	39	235	18	110	18	4	F05	14 x 18	6,70
A954256	50	150	165	105	49	271	20	125	18	4	F05	14 x 18	8,90