

	<p>DN15-DN50</p> <p>CE </p>
	<p>DN65-DN100</p> <p>CE </p>
	<p>DN125-DN150</p> <p>CE </p>
	<p>DN200-DN300</p> <p>CE </p>



Radna temperatura: -20 °C/+60 °C**Materijali**

1	Kučiče	Nodularni liv – EN-GJS-400-15 (GGG40)
2	Kugla	Nerdjajući čelik – X5CrNi18-10
3	Vretno	Nerdjajući čelik – X20Cr13
4	Zaptivač	PTFE
5	O-Ring	Viton
6	Ručka	Čelik – AISi8, S235JR (RSt 37-2)

KPN-G DN ... PN16 DP VX PX**PN16**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak ØSxP/K	Težina (kg)
A950001	15	115	95	72	13	158	16	65	14	4	F03	14x10	3,10
A950002	20	120	105	82	19,5	158	18	75	14	4	F03	14x10	3,30
A950003	25	125	115	83	25	158	18	85	14	4	F04	14x10	3,80
A950004	32	130	140	102	32	180	18	100	18	4	F05	17,8x14	5,80
A950005	40	140	150	107	40	180	18	110	18	4	F05	17,8x14	7,00
A950006	50	150	165	116	50	222	20	125	18	4	F05	18x14	9,40
A950007	65	170	185	140	63,5	293	18	145	18	4	F07	23,8x19	15,20
A950008	80	180	200	150	78	293	20	160	18	8	F07	23,8x19	19,10
A950009	100	190	220	166	99	415	20	180	18	8	F07	23,8x19	27,30
A950010	125	325	250	241	124	600	22	210	18	8	F10	31,6x19	55,00
A950011	150	350	285	258	149	600	22	240	22	8	F10	31,6x19	72,00
A950012	200	400	340	–	200	–	24	295	22	12	F12	K30	144,00
A950013	250	450	405	–	250	–	26	355	26	12	F14	K36	235,00
A950014	300	500	460	–	300	–	29	410	26	12	F14/16	K36	329,00

KUGLIČNI LEŽAJ

KPN-G DN ... PN40 DP VX PX**PN40**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak ØSxP/K	Težina (kg)
A951001	15	115	95	72	13	158	16	65	14	4	F03	14x10	3,10
A951002	20	120	105	82	19,5	158	18	75	14	4	F03	14x10	3,30
A950159	25	125	115	83	25	158	18	85	14	4	F04	14x10	3,80
A950173	32	130	140	102	32	180	18	100	18	4	F05	17,8x14	5,80
A950172	40	140	150	107	40	180	18	110	18	4	F05	17,8x14	7,00
A950959	50	150	165	116	50	222	20	125	18	4	F05	18x14	9,40
A950081	65	170	185	140	63,5	293	18	145	18	8	F07	23,8x19	15,20
A950157	80	180	200	150	78	293	20	160	18	8	F07	23,8x19	19,10
A951229	100*	190	235	166	99	380	20	190	22	8	F07	M24x17	39,00

Radna temperatura: -20 °C/+60 °C**Materijali**

1	Kučiče	Nodularni liv – EN-GJS-400-15 (GGG40)
2	Kugla	Mesing – CuZn40Pb2 (Ms 58)
3	Vretno	Nerdjajući čelik – X5CrNi18-10
4	Zaptivač	PTFE
5	O-Ring	Viton
6	Ručka	Čelik – AISi8, S235JR (RSt 37-2)

KPN-G DN ... PN16 DP VX PB**PN16**

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	ISO (gornja) prirubnica	Nastavak ØSxP/K	Težina (kg)
A950403	25	125	115	83	25	158	18	85	14	4	F04	14x10	3,80
A950404	32	130	140	102	32	180	18	100	18	4	F05	17,8x14	5,80
A950405	40	140	150	107	40	180	18	110	18	4	F05	17,8x14	7,00
A950406	50	150	165	116	50	222	20	125	18	4	F05	18x14	9,40
A950407	65	170	185	140	63,5	293	18	145	18	4	F07	23,8x19	15,20
A950408	80	180	200	150	78	293	20	160	18	8	F07	23,8x19	19,10
A950409	100	190	220	166	99	415	20	180	18	8	F07	23,8x19	27,30
A950410	125	325	250	241	124	600	22	210	18	8	F10	31,6x19	55,00
A950411	150	350	285	258	149	600	22	240	22	8	F10	31,6x19	72,00

Napomena

Ugradbena dužina odgovara standardu DIN3202 F18. DN50 do DN300 s opružnim zaptivačma.

DN200 – DN300 s ručnim pužnim pogonom.

HTB od DN25 do DN100.

Antistatički dizajn i požarni zaptivač.

*Kučiče iz čelika – A105.